



CA9308DKM0



CANNAREGIO PROOFER
for SQUERO DECK OVENS
8 TRAYS 600 x 400 - GN 1/1
MECHANICAL CONTROL



FUNCTIONAL CHARACTERISTICS

Overlapping oven	SQDK01* SQDK02*
Display	Analogic
Supply	Electric
Timer	-
Max proofing temperature (°C)	60 °C
Core probe	-
Cooking chamber material	AISI430
Opening door	Double door

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	Sheet PA-BIV 4/80 mm
Max tray load	4 [kg]

DIMENSIONS

Size with handle WxDxH (mm)	935x925x620 mm
Chamber size WxDxH (mm)	608x875x385 mm
Unit weight (Kg)	48 kg

PACKAGING

Packaging	PALLET + CARTON BOX
Packaging size WxDxH (mm)	985x1005x645 mm
Unit weight with packaging (Kg)	63 kg
Crate packaging size (optional)	-

ELECTRICAL DATA

HEATERS 1,3kW (240 V)	
Power	2,4kW
Frequency	50/60Hz
Power supply	220-240V 1N~
Amperage	10,4A
Power cord req.	3G1,5



WATER CONNECTION REQUIREMENTS

Humidification Water inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

CONNECTIVITY

USB	-
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA

