



# VACUUM SEALER SU-520L

Tabletop model. 20 m<sup>3</sup>/h. 555 mm.



FOOD PRESERVATION AND SOUS-VIDE  
COMMERCIAL VACUUM PACKING MACHINES

## SALES DESCRIPTION

555 mm sealing bar.  
20 m<sup>3</sup>/h Busch vacuum pump.  
Vacuum controlled by sensor.

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 99-programme memory. Blocking option.
- ✓ "Pause" button to marinate food.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Bag sealing program.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.

## INCLUDES

- ✓ Busch pump.
- ✓ Sensor controls.
- ✓ Programmable.
- ✓ Bluetooth connectivity.
- ✓ Vacuum plus: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ Pause function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF approved.
- ✓ Filling plate.

## OPTIONAL

- Inert gas.
- Sealing plus.
- Printer.
- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and accessories.
- Bag cutting kit.
- Support for liquid packaging.
- Additional filling plates.

## ACCESSORIES

- Bag cutting kits
- Filling plates
- Liquid insert plates
- Vac-norm external vacuum kit
- Vac-norm containers
- Smooth bags for vacuum packing
- Trolley for vacuum packing machines
- Thermal labels for CG2 / RB printer
- RB desktop printer for SU vacuum packing machines
- Thermal transfer labels for RB printer
- Vacuum packing machines maintenance kits

## SPECIFICATIONS

Pump capacity: 20 m<sup>3</sup>/h  
Pump capacity (60 Hz): 24 m<sup>3</sup>/h  
Bar length: 555 mm  
Total loading: 750 W  
Vacuum pressure (maximum): 2 mbar

### Internal dimensions

- ✓ Width: 568 mm
- ✓ Depth: 431 mm
- ✓ Height: 215 mm

### External dimensions (W x D x H)

- ✓ Width: 634 mm
- ✓ Depth: 552 mm
- ✓ Height: 513 mm
- Net weight: 70.4 kg
- Noise level (1m.): 75 dB(A)
- Background noise: 32 dB(A)
- Crated dimensions  
786 x 612 x 685 mm
- Gross weight: 79.8 kg





# VACUUM SEALER SU-520L

Tabletop model. 20 m<sup>3</sup>/h. 555 mm.



## AVAILABLE MODELS

1141136	SU-520GP+ L 120/60/1
1141112	SU-520P L 230/50-60/1
1141114	SU-520P+ L 230/50-60/1
1141115	SU-520GP L 230/50-60/1
1141117	SU-520GP+ L 230/50-60/1
1141131	SU-520P L 120/50-60/1
1141133	SU-520P+ L 120/50-60/1
1141134	SU-520GP L 120/50-60/1
1141139	SU-520GP L 230/50-60/1 AUS

\* Ask for special versions availability

FOOD PRESERVATION AND SOUS-VIDE  
COMMERCIAL VACUUM PACKING MACHINES

 **sammic** | [sammic.com](http://sammic.com)  
**Food Service Equipment Manufacturer**

Polígono Basarte, 1. phone +34 943 15 72 36  
 20720 Azkoitia, Spain [sales@sammic.com](mailto:sales@sammic.com)



Project	Date
Item	Qty
Approved	

product sheet  
updated 03/12/2025